VESTA-382

IRAGS-35SL-F1-2W-868

PIR and glass break detector

RADE 2

- PIR and glass break detector
- PIR range up to 12 meters, 90°
- Microphonic range up to 8 meters
- Anti-pet up to 25 kg
- Remote adjustable anti-pet sensitivity and immunity levels
- EN50131 Grade 2 certified



Reference / Model

VESTA-382 / IRAGS-35SL-F1-2W-868

Dual technology multi-function PIR and glass breakage detector

Combines a PIR motion detector with an acoustic glass break detector.

Its unique dual functionality is capable of detecting motion in a designated room and determining glass breakage.

Inheriting the advantages of its predecessor IR-35, IRAGS-35 offers remote control of sensitivity level and pet immunity settings

PIR range of up to 12 meters, 90°.

Microphonic range up to 8 meters (adjustable sensitivity: 8/5/3/1.5 meters)

Features a special lens made with advanced technology to help reduce blind spots

Immunity for pets up to 25 kg

Equipped with microphonic technology to recognize acoustic patterns and provide full glass breakage detection coverage

Alerts home and business owners when a window or glass door is being shattered or broken while monitoring the condition of the glass

868 MHz radio frequency



PIR and glass break detector



| Reference / Model | VESTA-382 / IRAGS-35SL-F1-2W-868 |
|---|----------------------------------|
| Periodic supervisory signals to check system integrity | |
| Temperature compensated sensitivity control | |
| Flexible installation height from 2.3 to 2.5 meters (8 to 8.5 feet) | |
| Powered by 3 CR123 lithium batteries | |
| Battery life of 5 years | |
| Operating temperature -10°C ~ +45°C (-10°C ~ +45°C) | |
| Relative humidity up to 85% (non-condensing) | |
| Dimensions: 69 (W) x 112 (H) x 37 mm | |
| EN50131 Grade 2 certified | |
| | |