

PIR and glass breakage detector V-MAX BUS



- Vesta V-MAX BUS PIR and glass breakage detector
- PIR range up to 12 meters, 90°
- Microphonic range up to 8 meters
- Anti-pets up to 25 kg
- Remote adjustable anti-pet sensitivity and immunity levels
- BUS power supply
- EN50131 Grade 2 certified

**Reference / Model****VESTA-397 / IRAGS-35-BUS**

PIR and glass breakage detector with V-MAX BUS technology

Combines a PIR motion detector with an acoustic glass breakage detector

Special lens to reduce blind spots and flexibility in installation height (2.3 ~ 2.5 meters)

Immunity to pets up to 25 kg

Remote control of sensitivity level and pet immunity

Unique dual functionality is capable of detecting motion in a designated location and determining glass breakage

Inheriting the advantages of its predecessor IR-35, IRAGS-35 offers remote control of sensitivity level and pet immunity settings.

PIR range of up to 12 meters, 90°.

Microphonic range up to 8 meters (adjustable sensitivity: 8/5/3/1.5 meters)

Equipped with microphonic technology for full glass breakage detection

Alerts home and business owners when a window or glass door is being shattered or broken while monitoring the glass condition

PIR and glass breakage detector V-MAX BUS

Reference / Model**VESTA-397 / IRAGS-35-BUS**

Connection to BUS devices via built-in terminals

Temperature compensated sensitivity control

Flexible installation height from 2.3 to 2.5 meters (8 to 8.5 feet)

Periodic supervisory signals to check system integrity

BUS power supply: 13.5V DC

Operating temperature from -10°C ~ +45°C

Relative humidity up to 85% (non-condensing)

Dimensions: 69 (W) x 112 (H) x 37 mm

EN50131 Grade 2 certified